




DESIGNED TO COMPACT ANY SURFACE, THE PLATE COMPACTOR IS PARTICULARLY USEFUL FOR COMPACTING INFILL IN TRENCHES AFTER CABLES AND PIPES HAVE BEEN LAID. IT PROVIDES A SOLID, UNIFORM SURFACE THAT LASTS OVER TIME. THE ATTACHMENT IS COMPLETE WITH FIXED COUPLING TO THE MACHINE.

SUITABLE FOR ALL NEEDS, MODELS RANGE FROM THE SMALLEST VERSION OF 1.5 TONNES UP TO A MAXIMUM CAPACITY OF 35 TONNES. THEY GET COMPACTING JOBS DONE FAST, WITH BENEFITS IN TERMS OF SAFETY, ESPECIALLY WHEN USED IN A TRENCH, SINCE THERE IS NO NEED FOR THE OPERATOR TO BE DIRECTLY IN THE WORKING AREA, AND RESULTS ARE QUICK AND CLEAN.



		TONS (LB)	1,5 - 4,5	4 - 10	5 - 10	7 - 14	10 - 22	4 - 12	10 - 35	15 - 40	20 - 40
	MOD.		PB201C	PB301C	PB 301.5C	PB401C	PB501C	PM202C	PM502C	PM602C	PM702C
A	MM		540	720	720	795	875	660	835	945	1020
B	MM		230	310	310	340	390	340	500	500	540
C	MM		420	560	560	570	680	380	540	650	680
D	MM		600	700	700	800	800	700	800	1200	1200
E	MM		300	400	450	500	600	480	500	600	700
 KG	WITHOUT COUPLING	KG	200	240	250	350	650	350	700	1000	1200
	HYDRAULIC FLUID FLOW RATE	L/MIN	20	45	45	65	90	45	90	100	130
	CENTRIFUGAL FORCE	KN	15	30	45	60	90	60	100	120	240
	VIBRATING UNIT	BAR	160	160	160	160	160	160	160	160	250
	BACKPRESSURE	BAR	7	7	7	7	7	7	7	7	7
	VIBRATION RATE	RPM/MIN	2.100	2.100	2.100	2.100	2.100	2.200	2.200	2.200	2.200
	€		•	•	•	•	•	•	•	•	•

OPT 	FLOW AND PRESSURE REGULATOR VALVE	€	•	•	•	•	STANDARD	•	STANDARD	STANDARD	STANDARD
OPT 1	POLE GRAPPLE	€	•	•	•	•	•	•	•	•	•
OPT 2	NARROW PLATE	€	•	•	•	•	•	•	•	•	•
OPT 3	PILE DRIVER PLATE	€	•	•	•	•	•	•	•	•	•
OPT 4	HOLE DRILLING BIT	€	•	•	•	•	-	•	-	-	-